



Air Stop

Directions:

1. Thoroughly clean and dry the damaged area. Completely deflate if an inflatable article.
2. When the damage is small (a pin hole or tear under 2 inches) apply a light coat of AirStop two or three times. Allow 5 minutes to dry between each application.
3. For heavier material, e.g. fabric backed vinyl or a vinyl boat, apply up to five coats allowing a 5 minute drying time between coats.
4. Ensure the AirStop is completely dry before resuming use of the article.
5. When the damage is more extensive, cut a patch (with rounded corners) using any vinyl material. Generously coat the damaged area spreading the Airstop at least 3/8" from the torn edges. Apply the patch and apply Airstop to all edges of the patch making a seal between patch and the item being repaired. Allow the article to dry at least 10 hours before using.

CONTENTS HARMFUL. DANGEROUS FUMES FORM WHEN MIXED WITH OTHER PRODUCTS. MAY IRRITATE SKIN. CONTENTS MAY CATCH FIRE.

Do not mix with other household chemicals.

Do not swallow.

Do not breathe fumes.

Do not get on skin or clothing.

Do not smoke.

Keep out of reach of children.

Wear a mask. Use only in a well-ventilated area. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor.

To open tube, puncture inner seal with a stick, nail or other disposable tool.

FIRST AID TREATMENT:

Contains Tetrahydrofuran, Cyclohexanone and Acetone.

If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If on skin, rinse well with water. If breathed in, move person to fresh air.